



CELDA DE CARGA AMPLIFICADA TSAMP



Linearità - Isteresi
 $\leq \pm 0.03\%$
 Linearity - Hysteresis



IP65

PRECISION	0.03 %
CARGAS NOMINALES (E_{max})	10 - 25 - 50 - 100 kg 200 - 300 - 500 kg 1 - 2 - 2.5 - 5 - 7.5 t
SENSIBILIDAD NOMINAL	4-20 mA (3 wires)
SENSIBILIDAD NOMINAL	± 5 V
SENSIBILIDAD NOMINAL	± 10 V
TOLERANCIA DE CALIBRACION	$< \pm 0.1$ %
EFECTO DE TEMPERATURA (10 °C)	
a) en cero	± 0.028 %
b) en sensibilidad	± 0.012 %
ALIMENTACION NOMINAL	
4-20 mA	12 - 24 Vdc
± 10 V	18 - 24 Vdc

INFORMACION TECNICA



CONTÁCTENOS:



71420703 - 71420711

COCHABAMBA:

Telf: (591) (4) 4256993 - 4500905

E-Mail: cochabamba@tritecbolivia.com



tritec SRL



tritecbolivia

SANTA CRUZ:

Telfs: (591) (3) 3369764 - 3345670

E-Mail: santacruz@tritecbolivia.com

LA PAZ:

Telfs: (591)(2) 2900833 - Telf/Fax: (591) (2)2900834

E-Mail: lapaz@tritecbolivia.com